

## Motorbike 2T Synth Scooter Street Race

### Description

Fully synthetic high-performance motor oil. Ensures maximum performance, lubrication, wear protection and engine cleanliness under all operating conditions. Offers excellent friction values, low smoke development and thus significantly increases the driving pleasure. Tested on engines with catalytic converters. Tested on racing machines.

### Properties

- high thermal stability
- residue-free combustion
- high wear resistance
- prevents the build-up of deposits
- self mixing
- good corrosion protection

### Specifications and approvals:

API TC • Husqvarna • ISO L-EGD • JASO FD

### Technical data

Density at 15 °C	0,875 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	50 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	9,1 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	98 °C DIN ISO 2592
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	rot / red

### Areas of application

For air and water-cooled 2-stroke engines with separate and mixture lubrication. Specifically for sporting applications. Self-mixing. Mixture ratio up to 1:100 according to the manufacturer's instructions.

### Application

For mixture lubrication, pour the contents of the can into the fuel tank and top up the fuel according to the mixing ratio. Mixing takes place automatically. For separate lubrication, pour the contents of the can in-



to the oil tank. Oil is mixed with fuel via the metering device.

### Available pack sizes

1 l Canister plastic	1053 D-BOOKLET
20 l Canister plastic	1054 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**