## **Product information**

PI 42/26/08/2020

# Motorbike 4T Synth 10W-50 Street Race



## **Description**

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines.



- high shear stability
- optimum stability to aging
- optimum lubrication under all operating conditions
- tested for the use with catalytic converters
- especially suitable for wet clutches
- quarantees low oil consumption
- excellent wear protection

## Specifications and approvals:

API SN PLUS • JASO MA2

#### **Technical data**

SAE class (engine oils) 10W-50 **SAE J300** Density at 15 °C 0,850 g/cm<sup>3</sup> DIN 51757 Viscosity at 40 °C 124 mm<sup>2</sup>/s ASTM D 7042-04 Viscosity at 100 °C 18.5 mm<sup>2</sup>/s ASTM D 7042-04 Viscosity at -30°C (MRV) < 60000 mPas **ASTM D 4684** 165 Viscosity index **DIN ISO 2909** 

Viscosity at -25°C (CCS) <= 7000 mPas

ASTM D 5293

Pour point -39 °C

DIN ISO 3016

Evaporation loss (Noack) 4,5 %

CEC-L-40-A-93

Flash point 230 °C

**DIN ISO 2592** 

Total base number 7,0 mg KOH/g

DIN ISO 3771

Sulfate ash 0,8 g/100g

DIN 51575

Color number (ASTM) L 2,0

DIN 51578



## Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

## **Application**

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

## Available pack sizes

| 1 l Canister plastic   | 1502<br>BOOKLET |
|------------------------|-----------------|
| 1 l Canister plastic   | 1751<br>JP      |
| 4 l Canister plastic   | 1686<br>BOOKLET |
| 20 l Canister plastic  | 1567<br>D-GB    |
| 20 l Canister plastic  | 20852<br>JP     |
| 60 l Drum sheet metal  | 1564<br>D-GB    |
| 205 l Drum sheet metal | 1569<br>D-GB    |
|                        |                 |

Our information is based on thorough research and may be considered reliable, although not legally binding.