

Product information

Motorbike 2T Basic Scooter Street

PI 26/26/04/2021



Description

High-performance motor oil based on selected mineral oils. Guarantees reliable lubrication and wear protection under normal operating conditions.

Properties

- high wear resistance
- guarantees clean spark plugs
- prevents the build-up of deposits
- self mixing
- good corrosion protection

Specifications and approvals:

API TC • ISO L-EGB • JASO FB

Technical data

Density at 15 °C	0,865 g/cm ³ DIN 51757
Viscosity at 40 °C	67,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,4 mm ² /s ASTM D 7042-04
Viscosity index	115 DIN ISO 2909
Pour point	-15 °C DIN ISO 3016
Flash point	130 °C DIN ISO 2592
Total base number	1,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,06 g/100g DIN 51575
Color / appearance	rot

Areas of application

For air and water-cooled 2-stroke engines with separate and mixture lubrication. Self-mixing. Mixture ratio up 1:50 according to the manufacturer's instructions.

Application

For mixture lubrication, pour the contents of the can into the fuel tank and top up the fuel according to the mixing ratio. Mixing takes place automatically. For separate lubrication, pour the contents of the can into the oil tank. Oil is mixed with fuel via the metering device.



Available pack sizes

1 l Canister plastic	1619 D-BOOKLET
1 l Canister plastic	21245 ALGERIEN-GB-ARAB-F
4 l Canister plastic	1237 D-GB-I-E-P
60 l Drum sheet metal	1633 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.