

E10 Additive

Description

State-of-the-art, ash-free fuel additive for improving combustion and faster acceleration in partial load range. Specially developed to compensate loss of performance from E10 fuel. Improves the vehicle acceleration and smoothness. Protects against high water content in the fuel. Compatible with all gasoline and additive qualities.



Properties

- outstanding corrosion protection
- higher performance gain
- better drivability
- improves acceleration
- tested for the use with catalytic converters
- contains no organometallic compounds
- cleans the fuel system

Technical data

| | |
|--------------------|-----------------------------------|
| Base | Additive mixture in carrier fluid |
| Color / appearance | light brown |
| Density at 15 °C | 0,825 g/cm ³ |
| Flash point | >63 °C |
| Odor | characteristic |
| Form | liquid |
| Viscosity at 40 °C | <7 mm ² /s |

Areas of application

Used as an additive in the fuel of all 2-stroke and 4-stroke gasoline engines, especially for motor vehicle engines. Also suitable for two-wheeled vehicles.

Application

One 150 ml can is sufficient for 35 to 70 l of fuel. Mix the contents of the can with the fuel. Mixing takes place automatically.

Available pack sizes

| | |
|------------------------|---------|
| 150 ml Can sheet metal | 21321 |
| | D-GB-CN |
| 150 ml Can sheet metal | 21421 |
| | GB-E |
| 150 ml Can sheet metal | 21473 |
| | DK-S |

Our information is based on thorough research and may be considered reliable, although not legally binding.