

Product information

Motorbike Speed Additive

PI 38/26/08/2020



Description

State-of-the-art, ash-free combination of agents with acceleration-enhancing, cleaning, dispersing and material-protecting properties. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions. Ensures increased driving enjoyment due to optimized performance. The engine starts easier and also runs smoother.

Properties

- higher performance gain
- improves the acceleration
- protects fuel against oxidation and aging
- cleans the fuel system
- prevents corrosion in the fuel system
- prevents carburetor icing
- increases operational reliability

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier fluid
Color / appearance	gelb, klar / yellow, clear
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 40 °C	<7 mm ² /s
Density at 20 °C	0,814 g/cm ³
Hazard class as per German VbF	A III
Flash point	>61 °C

Areas of application

Added to the fuel of all 4-stroke and 2-stroke gasoline engines.

Application

Add into the fuel tank. For optimum effect, add every time you refuel. Fully compatible with all grades of gasoline fuel. Contents of can are sufficient to treat up to 20 liters of fuel.



Available pack sizes

150 ml Can sheet metal	3040
	D-GB-E
150 ml Can sheet metal	5920
	D-F-I-GR
150 ml Can sheet metal	20860
	JP

Our information is based on thorough research and may be considered reliable, although not legally binding.