Product information

PI 37/12/01/2021

Brake Anti-Squeal Paste (can with brush)



Description

Specially developed lubricating and separating paste made from synthetic and ceramic agents. Eliminates squealing noises that occur between brake pistons or contact surfaces and the brake lining.

Properties

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- outstandingly adherent
- ideally suited as a separating paste

Technical data

Form pastelike, liquid

Color / appearance blue

Base synthetische u.

keramische Wirkstoffe

Operating temperature

nae +250 °C

range

-40 to +200 short term

als Schmierpaste / as

lubricating agent

-40 to +1200 °C

als Trennpaste / as

release agent

Flash point >210 °C
Odor slightly

Shelf life in original

missing translation

sealed container

24 Monate

Areas of application

For fitting, repair and maintenance work on brake systems. Used for basic lubrication and as a preventive measure against brake squeals. Highly suitable as a universal paste for numerous applications apart from brake systems.

Comment

Do not apply paste to the friction surface of the lining or the brake disk!

Application

With floating brake calipers, first clean all sliding surfaces, channels and contact surfaces using a brush or brake file. Next, clean the brake components with Rapid Cleaner (Part no. 3318). After evaporation of the solvents, apply the paste to the cleaned parts at all sliding surfaces, channels and contact surfaces.



Available pack sizes

200 ml Can aerosol 3074

D-GB-I-F

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Technical hotline: +49 (0)731/1420-871 www.liqui-moly.com